

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**

Appl. No. 09/713,163  
Reply to December 9, 2003 Office Action  
Page 2

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application.

**Listing of Claims:**

1. (Previously Presented) A tilt-latch for a sash window disposed within opposed guide rails on a master frame, the sash window comprises a top rail, a base and two stiles connected together at their extremities, the tilt-latch adapted for releaseably securing the sash window to the master frame, the tilt-latch comprising:

a housing adapted to be supported by the top rail, the housing having an outward end opening and a cover, the cover having opposed longitudinal peripheral edges;

a latch bolt disposed within the housing and having a nose adapted for engaging a respective one of the guide rails; and,

an actuator connected to the latch bolt and sized to be positioned over the entire cover, the actuator having opposed depending flanges, the flanges being positioned over the peripheral edges of the cover wherein the flanges slide along the peripheral edges when the latch bolt is retracted into the housing.

2. (Original) The tilt-latch of claim 1 further comprising means for biasing the latch bolt through the outward end opening.

3. (Canceled)

4. (Canceled)

Appl. No. 09/713,163  
Reply to December 9, 2003 Office Action  
Page 3

5. (Original) The tilt-latch of claim 1 wherein the housing is adapted for substantially flush installation in the top rail wherein the cover is positioned on the top rail, wherein the actuator slides along the cover when retracting the latch bolt into the housing exposing a front segment of the cover.

6. (Original) The tilt-latch of claim 1 wherein the latch bolt has a slot and the actuator has a post, the post being received by the slot.

7. (Original) The tilt-latch of claim 6 wherein latch bolt has a finger extending into the slot and the actuator post has a tab, the tab engaging an underside of the finger.

8. (Original) The tilt-latch of claim 6 wherein the cover has an elongated opening wherein the post extends through the elongated opening and into the slot.

9. (Original) The tilt-latch of claim 6 wherein the actuator has a pair of ridges depending from an underside of the actuator and extending from the post.

10. (Previously Presented) The tilt-latch of claim 1 wherein the actuator has an underside surface, the underside surface having a recessed portion accommodating the cover of the housing.

11. (Previously Presented) The tilt-latch of claim 10 wherein the actuator is rectangular, the recessed portion being rectangular and corresponding in size to the cover.

12. (Previously Presented) The tilt-latch of claim 10 wherein the cover has a rear transverse edge that engages a rear transverse edge defined by the recessed portion of the actuator.

13. (Original) The tilt-latch of claim 1 wherein the actuator has a control button.

Appl. No. 09/713,163  
Reply to December 9, 2003 Office Action  
Page 4

14. (Original) The tilt-latch of claim 1 wherein the housing is adapted for substantially flush installation in the top rail and wherein the actuator slides along a top surface of the top rail when the latch bolt is retracted into the housing.

15. (Original) The tilt-latch of claim 1 wherein the actuator is made of metal.

16. (Original) The tilt-latch of claim 15 wherein the actuator is made of zinc.

17. (Original) The tilt-latch of claim 1 wherein the housing and latch bolt are made from plastic.

18. (Currently Amended) The tilt-latch of claim 1 wherein the biasing means comprises a spring.

19. (Original) The tilt-latch of claim 1 wherein the top rail has opposed header slots and the housing includes means for supporting the housing in the header slots.

20. (Previously Presented) The tilt-latch of claim 19 wherein each header slot defines a pair of header rails and the housing has sidewalls wherein the means for supporting comprises a longitudinal groove on each sidewall, the longitudinal groove receiving the header rail to support the housing in the top rail.

21. (Original) The tilt-latch of claim 1 wherein the housing further includes a depending tab engaging one of the stiles.

Appl. No. 09/713,163  
Reply to December 9, 2003 Office Action  
Page 5

22. (Currently Amended) A tilt-latch for a sash window disposed within opposed guide rails on a master frame, the sash window comprises a top rail, a base and two stiles connected together at their extremities, the tilt-latch adapted for releaseably securing the sash window to the master frame, the tilt-latch comprising:

a plastic housing adapted to be supported by the top rail, the housing having an outward end opening;

a plastic latch bolt disposed within the housing and having a nose adapted for engaging a respective one of the guide rails; and

means for biasing the latch bolt through the outward end opening; and

a metal actuator connected to the latch bolt.

23. (Canceled)

24. (Original) The tilt-latch of claim 22 wherein the actuator is made of zinc.

25. (Original) The tilt-latch of claim 22 wherein the housing has a cover and the actuator is sized to be positioned over the entire cover.

26. (Original) The tilt-latch of claim 25 wherein the cover has opposed longitudinal peripheral edges and the actuator has opposed depending longitudinal flanges, the flanges being positioned over the peripheral edges.

27. (Original) The tilt-latch of claim 26 wherein the flanges slide along the peripheral edges when the latch bolt is retracted into the housing.

Appl. No. 09/713,163  
Reply to December 9, 2003 Office Action  
Page 6

28. (Original) The tilt-latch of claim 25 wherein the actuator slides along the cover when retracting the latch bolt into the housing exposing a front segment of the cover.

29. (Original) The tilt-latch of claim 22 wherein the latch bolt has a slot and the actuator has a post, the post being received by the slot.

30. (Original) The tilt-latch of claim 29 wherein latch bolt has a finger extending into the slot and the actuator post has a tab, the tab engaging an underside of the finger.

31. (Original) The tilt-latch of claim 29 wherein the housing has a cover having an elongated opening wherein the post extends through the elongated opening and into the slot.

32. (Original) The tilt-latch of claim 22 wherein the actuator has a control button.

33. (Previously Presented) An actuator for a tilt-latch for a sash window disposed within opposed guide rails on a master frame, the sash window comprises a top rail, a base and two stiles connected together at their extremities, the tilt-latch adapted for releaseably securing the sash window to the master frame, the tilt-latch comprises a housing adapted to be supported by the top rail, the housing having an outward end opening and a cover, and a latch bolt disposed within the housing and having a nose adapted for engaging a respective one of the guide rails, the actuator comprising:

an elongated body connected to the latch bolt and sized to be positioned over the entire cover, wherein the housing is adapted for substantially flush installation in the top rail, and wherein the cover is adapted to be positioned on the top rail, and wherein the actuator is adapted to

Appl. No. 09/713,163  
Reply to December 9, 2003 Office Action  
Page 7

slide along the cover when retracting the latch bolt into the housing exposing a front segment of the cover.

34. (Original) The tilt-latch actuator of claim 33 wherein the cover is adapted to have opposed longitudinal peripheral edges and the actuator has opposed depending longitudinal flanges, the flanges adapted to be positioned over the peripheral edges.

35. (Original) The tilt-latch actuator of claim 34 wherein the flanges are adapted to slide along the peripheral edges when the latch bolt is retracted into the housing.

36. (Canceled)

37. (Original) The tilt-latch actuator of claim 33 wherein the latch bolt is adapted to have a slot and the actuator has a post, the post adapted to be received by the slot.

38. (Original) The tilt-latch actuator of claim 33 wherein the elongated body is made of zinc.

39. (Original) A tilt-latch for a sash window disposed within opposed guide rails on a master frame, the sash window comprises a top rail, a base and two stiles connected together at their extremities, the top rail having opposed header slots, the tilt-latch adapted for releaseably securing the sash window to the master frame, the tilt-latch comprising:

a plastic housing having means for supporting the housing in the header slot, the housing having an outward end opening, the housing further having a cover and a pair of sidewalls depending from the cover, the cover having opposed longitudinal peripheral edges and an elongated opening positioned within the peripheral edges;

Appl. No. 09/713,163  
Reply to December 9, 2003 Office Action  
Page 8

a plastic latch bolt disposed within the housing and having a nose adapted for engaging a respective one of the guide rails, the latch bolt having a slot, the latch bolt further having a spring wall;

a spring having one end positioned abutting the spring wall and another end abutting the housing wherein the latch bolt is biased through the outward end opening; and,

a zinc actuator having a post that is received by the slot wherein the actuator is connected to the latch bolt, the actuator having a pair of opposed depending longitudinal flanges, the actuator being sized to be positioned over the entire the cover and wherein the flanges are positioned over the longitudinal peripheral edges of the cover and wherein the actuator slides along the cover when retracting the latch bolt into the housing.

40. (Currently Amended) A tilt-latch for a sash window disposed within opposed guide rails on a master frame, the sash window comprises a top rail, a base and two stiles connected together at their extremities, the tilt-latch adapted for releaseably securing the sash window to the master frame, the tilt-latch comprising:

a housing adapted to be supported by the top rail, the housing having an outward end opening and an inner wall; and

a latch bolt disposed within the housing and having a nose adapted for engaging a respective one of the guide rails, the latch bolt further having a protrusion; and,

wherein the latch bolt has an extended position wherein the nose of the latch bolt extends through the outward end opening and wherein the protrusion is spaced from the wall, and



Appl. No. 09/713,163  
Reply to December 9, 2003 Office Action  
Page 9

wherein the latch bolt has a retracted position wherein the protrusion engages the wall to maintain the latch bolt in the retracted position.

41. (Canceled)

42. (Previously Presented) A tilt-latch for a sash window disposed within opposed guide rails on a master frame, the sash window comprises a top rail, a base and two stiles connected together at their extremities, the tilt-latch adapted for releaseably securing the sash window to the master frame, the tilt-latch comprising:

a housing adapted to be supported by the top rail, the housing having an outward end opening and a cover;

a latch bolt disposed within the housing and having a nose adapted for engaging a respective one of the guide rails; and,

an actuator connected to the latch bolt and sized to be positioned over the entire cover, wherein the housing is adapted for substantially flush installation in the top rail wherein the cover is positioned on the top rail, wherein the actuator slides along the cover when retracting the latch bolt into the housing exposing a front segment of the cover.

43. (Previously Presented) A tilt-latch for a sash window disposed within opposed guide rails on a master frame, the sash window comprises a top rail, a base and two stiles connected together at their extremities, the tilt-latch adapted for releaseably securing the sash window to the master frame, the tilt-latch comprising:

Appl. No. 09/713,163  
Reply to December 9, 2003 Office Action  
Page 10

a housing adapted to be supported by the top rail, the housing having an outward end opening and a cover;

a latch bolt disposed within the housing and having a nose adapted for engaging a respective one of the guide rails, the latch bolt further having a slot; and,

an actuator positioned over the entire cover, the actuator having a post, the post being received by the slot to connect the latch bolt and the actuator.

44. (Previously Presented) The tilt-latch of claim 43 wherein latch bolt has a finger extending into the slot and the actuator post has a tab, the tab engaging an underside of the finger.

45. (Previously Presented) The tilt-latch of claim 43 wherein the cover has an elongated opening wherein the post extends through the elongated opening and into the slot.

46. (Previously Presented) The tilt-latch of claim 43 wherein the actuator has a pair of ridges depending from an underside of the actuator and extending from the post.

47. (Canceled)

48. (Previously Presented) A tilt-latch for a sash window disposed within opposed guide rails on a master frame, the sash window comprises a top rail, a base and two stiles connected together at their extremities, the tilt-latch adapted for releaseably securing the sash window to the master frame, the tilt-latch comprising:

a housing adapted to for substantially flush installation in the top rail, the housing having an outward end opening and a cover;

Appl. No. 09/713,163  
Reply to December 9, 2003 Office Action  
Page 11

a latch bolt disposed within the housing and having a nose adapted for engaging a respective one of the guide rails; and,

an actuator connected to the latch bolt and sized to be positioned over the entire cover, wherein the actuator slides along a top surface of the top rail when the latch bolt is retracted into the housing.

49. (Canceled)

50. (Previously presented) A tilt-latch for a sash window disposed within opposed guide rails on a master frame, the sash window comprises a top rail, a base and two stiles connected together at their extremities, the tilt-latch adapted for releaseably securing the sash window to the master frame, the tilt-latch comprising:

a plastic housing adapted to be supported by the top rail, the housing having an outward end opening and a cover with opposed longitudinal peripheral edges;

a plastic latch bolt disposed within the housing and having a nose adapted for engaging a respective one of the guide rails; and,

a metal actuator connected to the latch bolt, wherein the actuator is sized to be positioned over the entire cover, and wherein the actuator has opposed depending longitudinal flanges, the flanges being positioned over the peripheral edges of the cover whereby the flanges slide along the peripheral edges when the latch bolt is retracted into the housing.

51. (Previously Presented) A tilt-latch for a sash window disposed within opposed guide rails on a master frame, the sash window comprises a top rail, a base and two stiles connected

Appl. No. 09/713,163  
Reply to December 9, 2003 Office Action  
Page 12

together at their extremities, the tilt-latch adapted for releasably securing the sash window to the master frame, the tilt-latch comprising:

a plastic housing adapted to be supported by the top rail, the housing having an outward end opening and a cover with opposed longitudinal peripheral edges;

a plastic latch bolt disposed within the housing and having a nose adapted for engaging a respective one of the guide rails; and,

a metal actuator connected to the latch bolt, wherein the actuator is sized to be positioned over the entire cover, and wherein the actuator has opposed depending longitudinal flanges, the flanges being positioned over the peripheral edges of the cover whereby the actuator slides along the cover when retracting the latch bolt into the housing exposing a front segment of the cover.

52. (Canceled)

53. (Previously Presented) A tilt-latch for a sash window disposed within opposed guide rails on a master frame, the sash window comprises a top rail, a base and two stiles connected together at their extremities, the tilt-latch adapted for releasably securing the sash window to the master frame, the tilt-latch comprising:

a plastic housing adapted to be supported by the top rail, the housing having an outward end opening;

Appl. No. 09/713,163  
Reply to December 9, 2003 Office Action  
Page 13

a plastic latch bolt disposed within the housing and having a nose adapted for engaging a respective one of the guide rails, the latch bolt further having a slot and a finger extending into the slot; and

a metal actuator connected to the latch bolt, the actuator having a post, the post being received by the slot, the post having a tab, the tab engaging an underside of the finger.

54. (Previously Presented) A tilt-latch for a sash window disposed within opposed guide rails on a master frame, the sash window comprises a top rail, a base and two stiles connected together at their extremities, the tilt-latch adapted for releaseably securing the sash window to the master frame, the tilt-latch comprising:

a plastic housing adapted to be supported by the top rail, the housing having an outward end opening and a cover, the cover having an elongated opening;

a plastic latch bolt disposed within the housing and having a nose adapted for engaging a respective one of the guide rails, the latch bolt further having a slot; and

a metal actuator connected to the latch bolt, the actuator having a post wherein the post extends through the elongated opening and into the slot.

55. (Previously Presented) A tilt-latch for a sash window disposed within opposed guide rails on a master frame, the sash window comprises a top rail, a base and two stiles connected together at their extremities, the tilt-latch adapted for releaseably securing the sash window to the master frame, the tilt-latch comprising:

Appl. No. 09/713,163  
Reply to December 9, 2003 Office Action  
Page 14

a plastic housing adapted to be supported by the top rail, the housing having an outward end opening;

a plastic latch bolt disposed within the housing and having a nose adapted for engaging a respective one of the guide rails; and

a metal actuator connected to the latch bolt, the actuator having a control button.

56. (Previously Presented) An actuator for a tilt-latch for a sash window disposed within opposed guide rails on a master frame, the sash window comprises a top rail, a base and two stiles connected together at their extremities, the tilt-latch adapted for releasably securing the sash window to the master frame, the tilt-latch comprises a housing adapted to be supported by the top rail, the housing having an outward end opening and a cover having opposed longitudinal peripheral edges, and a latch bolt disposed within the housing and having a nose adapted for engaging a respective one of the guide rails, the actuator comprising:

an elongated body connected to the latch bolt and sized to be positioned over the entire cover, wherein the actuator has opposed depending longitudinal flanges, the flanges adapted to be positioned over the peripheral edges and slide along the peripheral edges when the latch bolt is retracted into the housing.

57. (Previously Presented) An actuator for a tilt-latch for a sash window disposed within opposed guide rails on a master frame, the sash window comprises a top rail, a base and two stiles connected together at their extremities, the tilt-latch adapted for releasably securing the sash window to the master frame, the tilt-latch comprises a housing adapted to be supported by the top

Appl. No. 09/713,163  
Reply to December 9, 2003 Office Action  
Page 15

rail and for substantially flush installation in the top rail, the housing having an outward end opening and a cover wherein the cover is adapted to be positioned on the top rail, and a latch bolt disposed within the housing and having a nose adapted for engaging a respective one of the guide rails, the actuator comprising:

an elongated body connected to the latch bolt and sized to be positioned over the entire cover, wherein the actuator is adapted to slide along the cover when retracting the latch bolt into the housing exposing a front segment of the cover.

58. (Previously Presented) An actuator for a tilt-latch for a sash window disposed within opposed guide rails on a master frame, the sash window comprises a top rail, a base and two stiles connected together at their extremities, the tilt-latch adapted for releasably securing the sash window to the master frame, the tilt-latch comprises a housing adapted to be supported by the top rail, the housing having an outward end opening and a cover, and a latch bolt disposed within the housing and having a slot and a nose adapted for engaging a respective one of the guide rails, the actuator comprising:

an elongated body connected to the latch bolt and sized to be positioned over the entire cover, the body having a post adapted to be received by the slot in the latch bolt.

Appl. No. 09/713,163  
Reply to December 9, 2003 Office Action  
Page 16

59. (Added) A tilt-latch for a sash window disposed within opposed guide rails on a master frame, the sash window comprises a top rail, a base and two stiles connected together at their extremities, the tilt-latch adapted for releaseably securing the sash window to the master frame, the tilt-latch comprising:

a plastic housing adapted to be supported by the top rail, the housing having an outward end opening and a cover;

a plastic latch bolt disposed within the housing and having a nose adapted for engaging a respective one of the guide rails; and,

a metal actuator connected to the latch bolt, wherein the actuator is sized to be positioned over the entire cover.